

DORSO-LUMBER POLYAXIAL SCREW - HA COATED (FOR 5.5MM ROD)



CAT. NO.	METAL	DORSO-LUMBER POLYAXIAL SCREW - HA COATED (FOR 5.5MM ROD)
640.632H	TT	GREENS (G3) POLYAXIAL SINGLE THREAD SCREW - Ø 5.5 MM X 40 MM LENGTH (FOR 5.5MM ROD) (TITANIUM) HA COATED
640.633H	TT	GREENS (G3) POLYAXIAL SINGLE THREAD SCREW - Ø 5.5 MM X 45 MM LENGTH (FOR 5.5MM ROD) (TITANIUM) HA COATED
640.634H	TT	GREENS (G3) POLYAXIAL SINGLE THREAD SCREW - Ø 5.5 MM X 50 MM LENGTH (FOR 5.5MM ROD) (TITANIUM)HA COATED
640.652H	TT	GREENS (G3) POLYAXIAL SINGLE THREAD SCREW - Ø 6.5 MM X 40 MM LENGTH (FOR 5.5MM ROD) (TITANIUM)HA COATED
640.653H	TT	GREENS (G3) POLYAXIAL SINGLE THREAD SCREW - Ø 6.5 MM X 45 MM LENGTH (FOR 5.5MM ROD) (TITANIUM)HA COATED
640.654H	TT	GREENS (G3) POLYAXIAL SINGLE THREAD SCREW - Ø 6.5 MM X 50 MM LENGTH (FOR 5.5MM ROD) (TITANIUM)HA COATED

Specification

- Available in Dia 5.5mm & 6.5mm with Length 40,45 & 50mm.

Indication for use

HA Coated Poly Axial Screw is used for

- Hydroxyapatite is extensively used as a coating for improving the bio-activity of the metallic surfaces.
- The HA coated screws will help in growth of bone, such as the fusion will be quick.
- Used in different procedures to provide fixation.
- It is a Spine Fixation System Intended for use as a pedicle Screw fixation or as an Anterolateral spine fixation system.

