



LAG SCREW		
SR. NO.	PRODUCT DESCRIPTION	MAT.
1	LAG SCREW PRIMARY USE FOR DHS Ø 10 X 35 MM	TT
2	LAG SCREW PRIMARY USE FOR DHS Ø 10 X 40 MM	TT
3	LAG SCREW PRIMARY USE FOR DHS Ø 10 X 45 MM	TT
4	LAG SCREW PRIMARY USE FOR DHS Ø 10 X 50 MM	TT
5	LAG SCREW PRIMARY USE FOR DHS Ø 10 X 55 MM	TT
6	LAG SCREW PRIMARY USE FOR DHS Ø 10 X 60 MM	TT
7	LAG SCREW PRIMARY USE FOR DHS Ø 10 X 65 MM	TT
8	LAG SCREW PRIMARY USE FOR DHS Ø 10 X 70 MM	TT
9	LAG SCREW PRIMARY USE FOR DHS Ø 10 X 75 MM	TT
10	LAG SCREW PRIMARY USE FOR DHS Ø 10 X 80 MM	TT
11	LAG SCREW PRIMARY USE FOR DHS Ø 07 X 25 MM	TT
12	LAG SCREW PRIMARY USE FOR DHS Ø 07 X 30 MM	TT
13	LAG SCREW PRIMARY USE FOR DHS Ø 07 X 35 MM	TT
14	LAG SCREW PRIMARY USE FOR DHS Ø 07 X 40 MM	TT
15	LAG SCREW PRIMARY USE FOR DHS Ø 07 X 45 MM	TT
16	LAG SCREW PRIMARY USE FOR DHS Ø 07 X 50 MM	TT

Specification

- Product is available in Titanium material.

Indication for use

- The Paediatric Lag Screw is indicated for fixation of fractures and osteotomies in paediatric patients. It is designed to provide interfragmentary compression and stable fixation while accommodating the anatomy of growing bones. The screw helps maintain fracture reduction and promotes bone healing. It is suitable for use in paediatric trauma and reconstructive orthopaedic procedures.

